



MINI LIGHTBARS MINI LEGEND




Federal Signal Vama develops and introduces the new, low-profile **Legend Solaris 24" Mini lightbar**. It provides a 360-degree coverage and superior off-axis warning and increased up-time for your fleet. On the other hand, Legend Solaris 24" Mini lightbar offers, in minimum space, technological advantages thanks to its special design:

- **ROC TECHNOLOGY (Reliable Onboard Circuitry)**. ROC technology eliminates 85% of potential failure points in the lightbar, reducing repair costs and increasing the hours your emergency vehicles stay on the road. ROC incorporates a printed circuit board in one assembly to reduce the amount of electrical connections found in a typical lightbar.


- **360 DEGREE COVERAGE**. Solaris technology and ROC design provides exceptional 360 degree coverage, which results in the elimination of any dark spots and superior off-axis warning around the lightbar.

- **INCREASED SECURITY**. Better grip, stability and security to the vehicle on the road due to its less aerodynamic drag.

- **COST SAVINGS**. Less fuel consumption thanks to its low-profile and improved aerodynamics. Furthermore, ROC technology reduces repairing costs and it allows more vehicle rotation on the road.



Mini-Legend Solaris dimensions (mm).



Voltage:	12/24 V
Operating temperature:	-20°C to 50°C
Average consumption (flashing mode):	3.5 Amp (12V) / 2.5 Amp (24V)
LEDs colours:	Blue, amber and red
Lens colours:	Blue, amber and red
Dimensions:	616 x 284 x 64 mm
Weight:	7.500 g



REF.	MOD.	DESCRIPTION
------	------	-------------

Legend 24" mini-lightbar (616 mm), 18 Solaris modules LED lights, non configurable, no CANBUS.

Magnetic mount

2059193	LGD24 PP FM	Legend Solaris Series lightbar, 616 mm, amber-amber, magnetic mount, cigarette plug, bitension, R65 class 1 approval.
2059154	LGD24 BB FM	Legend Solaris Series lightbar, 616 mm, blue-blue, magnetic mount, cigarette plug, bitension R65 class 1 and class 2 approval.
2059191	LGD24 RR FM	Legend Solaris Series lightbar, 616 mm, red-red, magnetic mount, cigarette plug, bitension R65 class 1 and class 2 approval.
2059195	LGD24 RB FM	Legend Solaris Series lightbar, 616 mm, red-blue, magnetic mount, cigarette plug, bitension.
2059197	LGD24 RP FM	Legend Solaris Series lightbar, 616 mm, red-amber, magnetic mount, cigarette plug, bitension.
2059199	LGD24 BP FM	Legend Solaris Series lightbar, 616 mm, blue-amber, magnetic mount, cigarette plug, bitension.

*Maximum speed for this model on the roof of the vehicle 200 km/h

Permanent mount

2059194	LGD24 PP FP	Legend Solaris Series lightbar, 616 mm, amber-amber, wiring harness, permanent mount, bitension, R65 class 1 approval.
2059155	LGD24 BB FP	Legend Solaris Series lightbar, 616 mm, blue-blue, wiring harness, permanent mount, bitension, R65 class 1 and class 2 approval.
2059192	LGD24 RR FP	Legend Solaris Series lightbar, 616 mm, red-red, wiring harness, permanent mount, bitension R65 class 1 and class 2 approval.
2059196	LGD24 RB FP	Legend Solaris Series lightbar, 616 mm, red-blue, wiring harness, permanent mount, bitension.
2059198	LGD24 RP FP	Legend Solaris Series lightbar, 616 mm, red-amber, wiring harness, permanent mount, bitension.
2059200	LGD24 BP FP	Legend Solaris Series lightbar, 616 mm, blue-amber, wiring harness, permanent mount, bitension.