



The **VisiBeam® II** is a high power spotlight with a handheld control unit.

For effective work area illumination, Federal Signal Vama's **VisiBeam® II** high power spotlight features a handheld remote control with pinpoint accuracy.

The spotlight uses the combination of a highly polished parabolic reflector and halogen bulb to produce a clear, even lightbeam that exceeds both "spot" and "flood" sealed beams. This powerful light is also energy efficient. The 55-Watt version draws only 4.2 amps when operating.

The VisiBeam II spotlight assembly is adjustable upwards 105° and downwards 35° from the horizontal, and can rotate a complete 360°. For pinpoint placement of the lightbeam, the assembly moves gradually at first and then speeds up. This "graduated start" enables the user to move the light in small increments.

The VisiBeam II's compact remote control can be operated from the palm of your hand or mounted on the vehicle dash. This is a great alternative to bulky manual spotlight controls in the cab of the vehicle. An indicator light on the control reminds the user that the spotlight is on.

Installation is quick and easy. The compact control fits virtually anywhere and can be mounted with Velcro or a more secure "snap holder" (both are included). The control is connected to the light via a 15' "telephone" type cable. The light itself has three mounting options available: permanent, magnetic, or pipe.

QUICK REFERENCE

FEATURES

- Brilliant work area lighting.
- Handheld control unit.
- "Graduated start" for pinpoint accuracy.
- Energy efficient.
- Rotates a full 360°.
- Horizontally and vertically adjustable.
- Dome easily removed.

APPLICATIONS

- Scene lighting.
- Work area lighting.

REPLACEMENT PARTS

Bulb, 55 W	8107152A
Bulb, 65 W	8107190A
Bulb, 100 W	8107158A
Dome	8433001A
Control cable	146903A


VISIBEAM® II SPOTLIGHT

HOW TO ORDER

1. Specify model.

- VB12S** 55-Watt halogen spotlight assembly with permanent mount kit.
- VB12S1** 100-Watt halogen spotlight assembly with permanent mount kit.
- VB12M** 55-Watt halogen spotlight assembly with magnetic mount and cigarette lighter plug with 10' cord.
- VB12M1** 100-Watt halogen spotlight assembly with magnetic mount and cigarette lighter plug with 10' cord.
- VB12P1** 100-Watt halogen spotlight assembly with pipe mount kit.
- VB24S** 65-Watt, 24V halogen spotlight assembly with permanent mount kit.
- VB24M** 65-Watt, 24V halogen spotlight assembly with magnetic mount and cigarette lighter plug with 10' cord.

MOUNTING DIAGRAM



FACTORY SET SPECIFICATIONS			
Model	Volts	Lamp	Current Draw
VisiBeam II	12 V	55 W	4.2 amps @ 12.8 V
	24 V	65 W	2.7 amps @ 24.0 V
	12 V	100 W	7.8 amps @ 12.8 V

DIMENSIONS						
MODEL	DIAMETER		HEIGHT*		SHIP. WEIGHT**	
	inches	cm	inches	cm	lbs	kg
VisiBeam II	6.5	16.5	6.6	16.5	1.5	0.7

* 6.9 inches (17.5 cm) for magnetic mount models.

7.3 inches (18.4 cm) for pipe mount models

** Surface mount. Other mount 2.0 lbs. (0.9 Kg).



An Iso 9001 Certified Company
FEDERAL SIGNAL VAMA, S.A.
 Dr. Ferrán, 7
 08339 VILASSAR DE DALT
 BARCELONA (Spain)
 Phone 34 93 741 79 32
 Fax 34 93 750 78 23
 email: marketing@vama.es
 Web : www.fedsig.vama.es

