



61" (1549 mm) Lightbar, amber color, ref. 2061007PL

61"




61" (1549 mm) Lightbar, amber color, ref. 2061008PL

61"




70" (1778 mm) Lightbar, amber color, ref. 2061010PL

70"



70" (1778 mm) Lightbar, amber color, ref. 2061002PL

70"





Amber Main lights according to R65 Regulation **W**

Amber Extra lights modules synchronized with main lights (front and rear)



White LEDs Central sign

Amber take down lights for rear flashing

Red take down lights

Empty module

* Bitension (12/24V) and wiring harness 5 meters long

Technical Specs.

White work lights

Electrical potencial:	12 V	24V
Operating temperature:	-20 a +50°C	
Current draw:		
Main lights	2,5A	1,5A
3 LEDS module WHITE	0,4A	0,25A
3 LEDS module AMBER	0,15A	0,10A
2 LEDS module RED	0,2A	0,13A
1 LED module AMBER	0,1A	0,07A
1 LED central sign (front and rear)	0,40A	0,20A
Colours of LEDs	Amber, red, white	
Colours of lenses	Amber and clear	



ISO 9001:2008 Certified Company Dr. Ferrán, 7 - 08339 VILASSAR DE DALT BARCELONA - SPAIN Phone 93 741 79 00 - Fax 93 750 78 23 Email: marketing@vama.es

www.fedsigvama.com





SOLARIS SOLARIS



Lightbar



SOLARIS

AURUM Series amber lightbars from Federal Signal Vama have been specially designed to meet different market needings, and could be fitted on garbage trucks, cleaners and sweepers, tow recovery, construction, road service and assistance, special convoys, etc., providing the high performance and efficiency of Solaris **Technology**. Traditional light systems spread it in a random direction, LED Solaris Technology reflects a strong light beam where it is needed most, on a wide angle, avoiding dark spots.





FULL LED. Amber lightbar with Solaris Technology provides exceptional 360 degrees coverage, achieving a superior offaxis warning around lightbar.



LOW PROFILE. Aerodynamic design.



INCREASED SECURITY. Better grip, stability and security to the vehicle on the road due to its less aerodynamic drag.



COST SAVINGS. Less fuel consumption thanks to its low-profile and improved aerodynamics.



ANALOG. Easy wiring connection and installation.



PERMANENT MOUNTING. Included in all lightbar configurations.


Approvals

Aurum Series is approved according to R65 main lights and R10 Electromagnetic Compatibility Regulations.

PRESELECT MODELS

24" (609 mm) Lightbar, amber colour, ref. 2061012PL / with day/night option, ref. 2061012PL/DN








32" (812 mm) Lightbar, amber colour, ref. 2061018PL

32"





Amber Main lights according to R65 Regulation




Amber Extra lights modules synchronized with main lights (front and rear)



White LEDs Central sign





45"

53"


53"

53"


53"

61"


53" (1346 mm) Lightbar, amber colour, ref. 2061005PL / with day/night option, ref. 2061005PL/DN



53" (1346 mm) Lightbar, amber colour, ref. 2061004PL / with cruise light option, ref. 2061004PLCR




53" (1346 mm) Lightbar, amber colour, ref. 2061003PL



NEW


53" (1346 mm) Lightbar, amber colour, ref. 2061021PL

61" (1549 mm) Lightbar, amber colour, ref. 2061009PL / with day/night option, ref. 2061009PL/DN





White work lights





Red take down lights



* Bitension (12/24V) and wiring harness 5 meters long

Empty module